IN THE CLAIMS

 (Currently Amended) A method comprising: delivering an electrical signal to a first position in or adjacent to a <u>first</u> cardiac chamber;

sensing a potential generated by the delivered electrical signal at a second position in or adjacent to a second cardiac chamber; and

determining a parameter related to cardiac geometry based, at least in part, on the sensing.

- 2. (Original) The method of claim 1, wherein the delivering delivers the electrical signal using a unipolar configuration.
- 3. (Original) The method of claim 1, wherein the first position is in a right ventricle or in a vessel.
- 4. (Original) The method of claim 1, wherein the delivering delivers the electrical signal using a ring electrode.
- 5. (Original) The method of claim 1, wherein the second position is in a vessel.
- 6. (Original) The method of claim 1, wherein the second position is in a cardiac chamber.
- 7. (Original) The method of claim 1, wherein the sensing senses the potential using a unipolar configuration.
- 8. (Original) The method of claim 1, wherein the sensing occurs during a refractory period.

- 9. (Original) The method of claim 1, wherein the delivering occurs during a refractory period.
- 10. (Original) The method of claim 1, wherein the determining determines a ventricular volume.
- 11. (Original) The method of claim 1, wherein the determining determines a ventricular distance.
- 12. (Original) The method of claim 1, wherein the determining determines a left ventricular diameter.
- 13. (Original) The method of claim 1, wherein the parameter relates to a stage of congestive heart failure.
- 14. (Original) The method of claim 1, further comprising delivering cardiac therapy based, at least in part, on the sensing.
- 15. (Currently Amended) An apparatus comprising:

 means for delivering an electrical signal to a first position in or adjacent to a <u>first</u> cardiac chamber;

means for sensing a potential generated by the delivered electrical signal at a second position in or adjacent to a second cardiac chamber; and

means for determining a parameter based, at least in part, on the means for sensing wherein the parameter relates to cardiac geometry.

- 16. (Original) The apparatus of claim 15 wherein the means for delivering an electrical signal comprises a power source, a lead and an electrode.
- 17. (Original) The apparatus of claim 15 wherein the mean for sensing a potential comprises an electrode, a lead and a circuit.

PATENT

- 18. (Original) The apparatus of claim 15 wherein the means for determining a parameter comprises an implantable and programmable device.
- 19. (Currently Amended) An implantable cardiac system comprising: an implantable device having a case capable of acting as an electrode; one or more implantable leads having one or more electrodes wherein the one or more leads are connectable to the device; and

circuitry that is operative to deliver an electrical signal to a first electrode position in or adjacent to a <u>first</u> cardiac chamber, sense a potential generated by the delivered electrical signal at a second electrode position <u>in or adjacent to a second cardiac chamber</u>, and determine a parameter based, at least in part, on the sensing wherein the parameter relates to cardiac geometry.

- 20. (Original) The system of claim 19 wherein the one or more implantable leads comprises at least two leads including a first lead that is configured for placement in a right ventricle and a second lead that is configured for placement in a left ventricle.
- 21. (Original) The system of claim 20 wherein the circuitry is operative to deliver an electrical signal to a first electrode carried by the first lead, and to sense a potential generated by the delivered electrical signal at a second electrode carried by the second lead.
- 22. (New) A method comprising:

delivering an electrical signal to a first position in or adjacent to a cardiac chamber using a unipolar electrode configuration;

sensing a potential generated by the delivered electrical signal at a second position; and

determining a parameter related to cardiac geometry based, at least in part, on the sensing.